

ANGULAR

BOTANICA EDITION







QUILT DESIGNED BY AGEstudio

THE CURSTOR Stanica

FABRICS DESIGNED BY AGF STUDIO



Fabric A CUR8BT206 SEED SCATTER



BINDING CUR8BT207 BRANCH REFLECTIONS



Fabric C CUR8BT204 MOMENT OF ZEN AQUA



Fabric D CUR8BT205 SPRINKLED SPRIGS



Fabric E
CUR8BT200
BOTANICAL BREEZE



CUR8BT201 BRICK ROAD BLUSH



Fabric G CUR8BT203 WHITE NOISE FRESH



CUR8BT202 FOLIAGE DANCE





FINISHED SIZE | 56½" × 65½"

Please read all instructions thoroughly before beginning.

FABRIC REQUIREMENTS

Fabric A	CUR8BT206	½ yd.
Fabric B	CUR8BT207	1 yd.
Fabric C	CUR8BT204	½ yd.
Fabric D	CUR8BT204	½ yd.
Fabric E	CUR8BT200	½ yd.
Fabric F	CUR8BT202	½ yd.
Fabric G	CUR8BT203	3½ yd.

BACKING FABRIC CUR8BT201 4½ yds (Suggested)

BINDING FABRIC
Fabric B CUR8BT207 (Included)



CUTTING DIRECTIONS

Please ensure that all fabrics are ironed thoroughly before cutting them. ¼" seam allowances are included. WOF means width of the fabric.

Fabric A

• Cut 1 (one) 5" x WOF strip, then;

Sub-cut into 4 (four) 5" \times 9½" rectangles.

• Cut 6 (six) 1" x WOF strips.

Fabric **B**

Cut 3 (three) 5" x WOF strips, then;
 Sub-cut into 12 (twelve) 5" x 9½" rectangles.

• Cut 7 (seven) 21/2" x WOF strips.(BINDING)

Fabric C through F

• Cut 3 (three) 5" x WOF strips, then;

Sub-cut into 12 (twelve) 5" x 9½" rectangles

Fabric G

• Cut 16 (sixteen) 5" x WOF strips, then;

Sub-cut into 128 (one hundred and twenty eight) 5" squares.

Fabric H

• Cut 8 (eight) 5" x WOF strips, then;

Sub-cut into 8 (eight) 5" x 231/2" strips.

CONSTRUCTION

Sew all rights sides together with ¼" seam allowance.

Flying Geese Construction.

• Place 1 (one) 5" square from fabric ${\bf G}$ on the right edge of 1 (one) 5" x $9\frac{1}{2}$ " rectangle from fabric ${\bf A}$ and mark a diagonal line from the top left to the bottom right corner of the square. Sew on the drawn line and trim $\frac{1}{4}$ " away from the seam and press.



DIAGRAM 1

- Place another 5" square from fabric G on the left edge of the same piece, mark a diagonal line from the top right to the bottom left corner of the square and sew through the line.
- Trim 1/4" away from the seam and press.
- Each fliying geese unit should measure 5" x 91/2".




DIAGRAM 2

 Make a total of 2 (two) GAG flying geese combination.



DIAGRAM 3

 Repeat the Flying Geese Construction with the following fabic combinations: B-C-D-E and F.



x12





x12

GDG



x12

GEG



x12

GFG



x12

DIAGRAM 4

• Sew all flying geese units into 12 (twelve) rows of 5 (five) units each, then sew rows together.

Row 1	GBG	GEG	GFG	GEG	GBG
Row 2	GFG	GDG	GBG	GDG	GFG
Row 3	GEG	GCG	GFG	GCG	GBG
Row 4	GBG	GFG	GCG	GEG	GDG
Row 5	GCG	GDG	GEG	GCG	GEG
Row 6	GEG	GFG	GDG	GFG	GCG
Row 7	GFG GDG	GEG	GCG GEG	GBG	GDG GBG
Row 8	GCG	GDG	GDG	GDG GEG	GFG
Row 9	GBG	GFG	GCG	GCG	GEG
Row 10	GDG	GEG	GDG	GFG	GCG
Row 11	The second second		A CONTRACTOR		
Row 12	GCG	GBG	GBG	GBG	GFG

- Join all 6 (six) 1" x WOF strips from Fabric A, short ends together to make a long strip.
- Measure the length of each side of the quilt. Average those numbers and cut 2 border strip to that measurement or to 54½" long if quilt top is true to size. Sew to the sides of the quilt.



DIAGRAM 6

• Measure the top and bottom of the quilt. Average those numbers and cut 2 border strip to that measurement or to 46½" long if quilt top is true to size. Sew to the top and bottom of the quilt.



A 1" x 46½"

DIAGRAM 7

TOP ASSEMBLY

- Join 2 (two) 5" x 23½" strips from Fabric **G** with one **GAG** unit, as shown in the diagram below.
- Make a total of 2 (two) of these units.




DIAGRAM 8

• Sew the strips made in the diagram above to each long side of the quilt, as shown.



DIAGRAM 9

• Join 2 (two) 5" x 23½" strips from Fabric G with one GAG unit, as shown in the diagram below.

• Make a total of 2 (two) of these units.




DIAGRAM 10

 Sew the strips made in the diagram above to top and bottom of the quilt, as shown, making sure all edges are matched.



DIAGRAM 11

 See the pattern cover image for the finished quilt. Quilt as desired.



QUILT ASSEMBLY

Sew rights sides together.

- Place BACKING FABRIC on a large surface wrong side up. Stretch it with masking tape against that surface.
- Place BATTING on top of backing fabric.
- Place TOP on top of the batting with right side facing up. Smooth away wrinkles using your hands.
- Pin all layers together and baste with basting thread, using long stitches. You can also use safety pins to join the layers.
- Machine or hand quilt starting at the center and working towards the corners. Remember that quilting motifs are a matter of personal preference. Have fun choosing yours!
- After you finished, trim excess of any fabric or batting, squaring the quilt to proceed to bind it.

BINDING

Sew rights sides together.


• Sew 7 (seven) 2½" strips of fabric **B** to make a long strip. Start sewing the binding strip in the middle of one of the sides of the quilt, placing the strip right side down and leaving an approximated 5" tail. Sew with ¼" seam allowance (using straight stitch), aligning the strip's raw edge with the quilt top's raw edge.

• Stop stitching ¼" before the edge of the quilt (DIAGRAM B 1). Clip the threads. Remove the quilt from under the machine presser foot. Fold the strip in a motion of 45° and upward, pressing with your fingers (DIAGRAM B2). Hold this fold with your finger, bring the strip down in line with the next edge, making a horizontal fold that aligns with the top edge

of the quilt (DIAGRAM B3). Start sewing at $\frac{1}{4}$ " of the border, stitching all the layers. Do the

same in the four corners of the quilt.

- Stop stitching before you reach the last 5 or 6 inches. Cut the threads and remove the quilt from under the machine presser foot. Lay the loose ends of the binding flat along the quilt edge, folding the ends back on themselves where they meet. Press them together to form a crease. Using this crease as the stitching line, sew the two open ends of the binding with right sides together (you can help yourself marking with a pencil if the crease is difficult to see).
- Trim seam to ¼" and press open. Complete the sewing. Turn binding to back of the quilt, turn raw edge inside and stitch by hand using blind stitch.



• If you are using our 2.5 edition (binding fabric), click or scan this QR code to see a tutorial on how to use this specialty fabric.



Congratulations & enjoy



artgalleryfabrics.com

NOTE: While all possible care has been taken to ensure the accuracy of this pattern, We are not responsible for printing errors or the way in which individual work varies.

Please read instructions carefully before starting the construction of this quilt. If desired, wash and iron your fabrics before starting to cut.

© 2025 Courtesy of Art Gallery Quilts LLC. All Rights Reserved.